

WHAT IS CLAIMED IS:

1 1. A thin type permanent magnet generator that can be incorporated in a diskette,
2 comprising:

3 a disc-shaped rotor having a soft magnetic disc-shaped hub that is rotatable around
4 a rotational axis, and a flat ring-shaped permanent magnet concentrically fitted to an end of
5 the hub; the permanent magnet axially magnetized in such a manner as to have a plurality
6 of magnetic poles of alternately different polarities in the circumferential direction on each
7 end face thereof; the magnetic poles on one end face of the permanent magnet being
8 magnetically short-circuited with the hub, and the magnetic poles on the other end face
9 serving as rotor magnetic poles, and

10 a stator having a plurality of magnetic pole teeth having on an end thereof a
11 plurality of stator magnetic poles that can face the rotor magnetic poles at the same pole
12 intervals via an axial gap and extending radially outward from the stator magnetic poles;
13 the magnetic pole teeth connected at the other end to each other by a soft magnetic yoke and
14 having coils wound on the intermediate portions thereof;

15 the ratio of generator thickness/diagonal length of generator end face being not more
16 than 6 %.

1 2. A thin type permanent magnet generator as set forth in Claim 1, wherein the
2 outer periphery of the hub protrudes not less than 0.3 mm from the outer periphery of the
3 permanent magnet.

1 3. A thin type permanent magnet generator as set forth in Claim 2, wherein an end
2 of each of the stator magnetic poles on the side facing the rotor magnetic poles protrudes not
3 less than 0.3 mm radially inward to the central opening of the permanent magnet.

1 4. A thin type permanent magnet generator as set forth in Claim 1, wherein a
2 distance between portions of the adjacent stator magnetic poles facing the rotor magnetic
3 poles is 0.3 mm to 1.0 mm.

1 5. A thin type permanent magnet generator as set forth in Claim 3, wherein a
2 distance between portions of the adjacent stator magnetic poles facing the rotor magnetic
3 poles is 0.3 mm to 1.0 mm.

6. A thin type permanent magnet generator as set forth in Claim 1, wherein the magnetic pole teeth each have a step difference in the axial direction between the portion facing the rotor magnetic pole and the portion having a coil wound thereon; the overall thickness being reduced by the step difference.

7. A thin type permanent magnet generator as set forth in Claim 5, wherein the magnetic pole teeth each have a step difference in the axial direction between the portion facing the rotor magnetic pole and the portion having a coil wound thereon; the overall thickness being made thinner by the step difference.

8. A thin type permanent magnet generator as set forth in Claim 6, wherein the magnetic pole teeth each have an inclined portion at the step difference; the inclined portion having a 30 to 60° angle with respect to the longitudinal direction of the entire magnetic pole teeth.

9. A thin type permanent magnet generator as set forth in Claim 7, wherein the magnetic pole teeth each have an inclined portion at the step difference; the inclined portion having a 30 to 60° angle with respect to the longitudinal direction of the entire magnetic pole teeth.

10. A thin type permanent magnet generator as set forth in Claim 1, wherein the permanent magnet is a bonded magnet containing SmFeN magnetic powders or NdFeB magnetic powders, or a sintered NdFeB magnet.

11. A thin type permanent magnet generator as set forth in Claim 9, wherein the permanent magnet is a bonded magnet containing SmFeN magnetic powders or NdFeB magnetic powders, or a sintered NdFeB magnet.

12. A thin type permanent magnet generator as set forth in Claim 10, wherein the permanent magnet is a bonded NdFeB magnet containing NdFeB magnetic powders.

13. A thin type permanent magnet generator as set forth in Claim 11, wherein the permanent magnet is a bonded NdFeB magnet containing NdFeB magnetic powders.

14. A thin type permanent magnet generator as set forth in Claim 1, wherein the hub is supported by an anti-friction bearing so as to be rotatable around the rotational axis.

15. A thin type permanent magnet generator as set forth in Claim 13, wherein the hub is supported by an anti-friction bearing so as to be rotatable around the rotational axis.

1 33. A diskette as set forth in Claim 31, wherein the permanent magnet is a bonded
2 magnet containing SmFeN magnetic powders or NdFeB magnetic powders, or a sintered
3 NdFeB magnet.

1 34. A diskette as set forth in Claim 32, wherein the permanent magnet is a bonded
2 NdFeB magnet containing NdFeB magnetic powders.

1 35. A diskette as set forth in Claim 33, wherein the permanent magnet is a bonded
2 NdFeB magnet containing NdFeB magnetic powders.

1 36. A diskette as set forth in Claim 20, wherein the hub is supported by an anti-
2 friction bearing so as to be rotatable around the rotational axis.

1 37. A diskette as set forth in Claim 35, wherein the hub is supported by an anti-
2 friction bearing so as to be rotatable around the rotational axis.

1 38. A diskette as set forth in Claim 36, wherein the portion of the hub which comes
2 in contact with balls of the anti-friction bearing has a hardness of not less than HRC35.

1 39. A diskette as set forth in Claim 37, wherein the portion of the hub which comes
2 in contact with balls of the anti-friction bearing has a hardness of not less than HRC35.

1 40. A diskette as set forth in Claim 38, wherein the portion of the hub which comes
2 in contact with balls of the anti-friction bearing has a U-shaped groove.

1 41. A diskette as set forth in Claim 39, wherein the portion of the hub which comes
2 in contact with balls of the anti-friction bearing has a U-shaped groove.

1 42. A diskette as set forth in Claim 20, wherein an engaging portion for engaging
2 with an external drive mechanism is provided on an end face of the hub; the engaging
3 portion comprising a central hole provided at the center of the hub and a recess provided at
4 a location displaced from the central hole on the hub surface;

5 the recess comprising a through hole provided on the hub and a recess provided on
6 the permanent magnet surface extending from the through hole.

1 43. A diskette as set forth in Claim 42, wherein a bottom plate made of a soft
2 magnetic material is fitted into the recess provided on the permanent magnet surface.

1 44. A diskette as set forth in Claim 20, wherein a memory card space is provided in
2 the diskette case adjacent to the permanent magnet generator, and the end face of the

- 3 permanent magnet generator which end face has the stator magnetic teeth is on the side of
- 4 the memory card space with respect to the disc-shaped rotor.